



Art. 006014

TUBI PER ALLACCI METANO, IN ACCIAO SALDATO CON RIVESTIMENTO IN POLIETILENE**METHANE SERVICE PIPES, WELDED STEEL WITH POLYETHYLENE COATING****APPLICAZIONE:**

Trasporto metano.

APPLICATION:

Conveying methane.

NORME PRODOTTO: UNI EN 10208-1**ACCIAIO**

tubi per condotte sono prodotti mediante saldatura longitudinale da nastro laminato a caldo con acciaio calmato L 235 GA.

RIVESTIMENTO ESTERNO

Rivestimento in polietilene.

Questo rivestimento presenta un alto potere isolante ed è applicato su tubazioni d'acciaio destinate ad essere interrate secondo norme UNI 9099.

PRODUCT STANDARDS: UNI EN 10208-1**STEEL**

Line pipe is produced by longitudinal welding from hot rolled strip with killed steel L 235 GA.

EXTERNAL COATING*Polyethylene coating.*

This coating has excellent insulating properties and is applied on steel piping for underground applications as per standard UNI 9099.

DN (inch)	DN	Diametro Diameter	Spessore Thickness	L (m)
3/4"	20	26.3	2.3	6
1"	25	33.6	2.9	6
1" 1/4	30	42.4	2.9	6
1" 1/2	40	48.3	2.9	6
2"	50	60.3	3.2	6
2" 1/2	65	76.1	3.2	6
3"	80	88.9	3.6	6
4"	100	114.3	4	6